



CCS Series Constant Current Shop

No charger is safer for your battery fleet.

USA Made!

Although ferroresonant technology has been around for many years, improvements are constantly being made and today, our charger boasts a high efficiency, 87% and power factor > .90% close to that of many other manufacturers high frequency chargers. Charge control monitors battery throughout the charge and delivers a safe, complete charge.



BENEFITS

Trustworthy ferroresonant technology.

Ideal for shop charging.

Available up to 40 Cells.

Single and three phase models

Charges wide range of batteries.




FEATURES

Fail Safe charge for your battery.

Automatic start and stop .

Designed to have a nearly flat curve.

Near constant current output while tapering slightly to maintain AC amp draw as battery voltage rises



Standard control 046-301

Rugged 16 GA. case 501
H: 26" x W: 24.25" x D: 24.625"

Max. Cells	Amp hr. Rating	DC Amps	SINGLE PHASE						
			Model	Control	AC Input Amps				Case
					120	208	240	480	
24	510	40	CCS24-510A1	046-0301	22.4	12.9	11.2	?	500
40	680	50	CCS36-680B1	046-0301	N/A	24.0	21.0	10.5	501
40	1000	75	CCS36-1000B1	046-0301	N/A	36.0	31.5	15.8	501
40	1350	100	CCS36-1350B1	046-0301	N/A	48.5	42.0	21.0	501
Max. Cells	Amp hr. Rating	DC Amps	THREE PHASE						
			Model	Control	AC Input Amps				Case
					120	208	240	480	
40	950	75	CCS36-950B3	046-0301	N/A	21.0	18.2	9.1	501
40	1400	100	CCS36-1400B3	046-0301	N/A	28.0	24.2	12.1	501
40	2000	150	CCS36-2000B3	046-0301	N/A	42.0	36.3	18.1	502



Charging Technologies, Inc
4328 Bridgeton Industrial Drive
Bridgeton, Missouri 63044

Phone: 314-739-1414
Fax: 314-739-1277
E-mail: sales@chargingti.com
www.chargingtechnologiesinc.com